

## PRODUCT DATA SHEET

# VALA SOLUTIONS PROTECT TAPE



**VALA SOLUTION PROTECT TAPE: ideal solution for a permanent, easy to apply sealant for leaking roofs and gutters. Covers roofs screws and nails.**

#### FEATURES & BENEFITS:

- no need for heat -sticks instantly
- does not crack -does not dry out. (no bitumen)
- high flexibility and movability
- no need for primer
- UV resistant; long lasting
- High quality butyl
- High wear and tear resistance
- Fills cracks.
- Protected by polyester /alu laminated foil.
- Easy to use : for DIY and professionals

#### TECHNICAL DATA:

TECHNICAL DATA:	
COLOURS	Black
COMPOSITION	PIB based / nontoxic /solvent free /no bitumen. Protected by a laminated polyester -aluminum foil
DIMENSIONS	Length: 30cm width: 5.5 cm thickness 1.5 mm
LIFE EXPECTANCY	Minimum 15 years
U.V. RESISTANCE	Excellent
SERVICE TEMPERATURE RANGE	-40 TO +90 °C Application between +4 to +40 °C
JOINT MOVEMENT	Up to 15%
COMPATIBILITY	Very good adhesion to most surfaces & compatible with most used construction materials. For further information, please contact our technical department
HOW TO USE	Remove the release paper. Press the product into position on the joint and close the surface by pushing firmly into place. Surface needs to be dry, dust free and clean. No primer or heat source
PACKAGING	Printed pouch with one strip of 30cm x 5.5 cm. 15 units per outer
WARNING	Not to be used for pressurized pipes (Oil and gas pipes).



(+27) 39 976 1114



16 Payne Street, Park Rynie  
4182, South Africa



info@butyltechnology.com



www.butyltechnology.com